

Proizvod / Product: HYDROSOL Classic

IZJAVA O USKLAĐENOSTI
DECLARATION OF CONFORMITY
Br. / No. 001/18-HDL

1. **Oznaka proizvoda / Unique identification code of product**
08.02.01

2. **Namjena proizvoda / Intended use**

Cementna malterna smjesa za vodonepropusnu zaštitu vanjskih i unutrašnjih horizontalnih i vertikalnih površina (CM) / Cementitious liquid-applied water impermeable product for interior and exterior horizontal and vertical surfaces (CM)

3. **Proizvođač / Manufacturer**

JUB d.o.o.
Dol pri Ljubljani 28
SI-1262 Dol pri Ljubljani
Slovenia

4. **Ovlašten predstavnik / Authorised representative**

JUB d.o.o. Sarajevo
Vlakovo 1J
71215 Blažuj
Bosna i Hercegovina
www.jub.ba

5. **Sistem ocjene usklađenosti / System of AVCP**

Sistem 3 / System 3

6. **Certifikacijsko tijelo / Certification body**

ZAG Ljubljana, 1404
Početno ispitivanje tipa, izvještaj br. / Initial type testing, Report No.
P 97/06-460-8
P 96/06-410-1

Nacionalni laboratorij za zdravje, okolje in hrano, Maribor

Ispitivanje materiala namenjenih za kontakt sa pitkom vodom / *Test report for products and materials coming into contact with foodstuffs and drinking water*

2131B-17/42229-18/2206

7. Deklarisana svojstva / *Declared performance*



Svojstvo / <i>Characteristic</i>	Deklaracija / <i>Declaration</i>	Tehnička specifikacija / <i>Technical specification</i>
Otpornost na pozitivan pritisak vode / <i>Resistance to positive water pressure</i>	nema prodora vode / <i>No water penetration</i>	EN 14891:2012 / AC 2012
Početna zatezna adhezivna čvrstoća / <i>Initial tensile adhesion strength</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012 / AC 2012
Zatezna adhezivna čvrstoća nakon tretiranja na 70°C / <i>Tensile adhesion strength after heat ageing</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012 / AC 2012
Zatezna adhezivna čvrstoća nakon tretiranja u vodi / <i>Tensile adhesion strength after water immersion</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012 / AC 2012
Zatezna adhezivna čvrstoća nakon zamrzavanja-odmrzavanja / <i>Tensile adhesion strength after freeze-thaw cycles</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012 / AC 2012
Sposobnost premoštavanja pukotina / <i>Crack bridging ability</i>	$\geq 0,75 \text{ mm}$	EN 14891:2012 / AC 2012
Procjena pogodnosti materiala za kontakt sa pitkom vodom / <i>Assessment of suitability of materials for contact to drinking water</i>	Odgovara / <i>Suitable</i>	OJRS, Art. 33 of Rules on Drinking Water OJRS, Art. 13 of Act Regulating the Sanitary Suitability of Materials Coming into Contact with Foodstuffs

Svojstva proizvoda navedena gore su u skladu sa deklariranim svojstvima. Za izdavanje izjave o usklađenosti je odgovoran isključivo gore naveden proizvođač.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Potpisao za i u ime proizvođača /

Signed for and on behalf of the manufacturer by:

Dol pri Ljubljani, 25.04.2018



Danijel Lisičić,
Vođa razvojnog područja